



Atrin Farazan Avin Ltd.

Sudadur™ Yellow-1322C (PbCrO₄)

SPECIFICATION

Chemical type: Lead Chrome Pigment

Color index Name: Pigment Yellow 34

Physical Form: Yellow Powder

Guaranteed Physical ANALYSIS

| PARAMETERS | OUR STANDARD | BLEEDING | OUR STANDARD |
|-------------------|----------------|-----------------------------|--------------|
| Oil absorption | 16 - 22 | Bleeding in Water | 5 |
| Specific Gravity | 6.7 ± 0.2 | Bleeding in 5% Caustic Soda | 5 |
| Bulk density g/ml | 0.8 ± 0.1 | Bleeding in 5% Hydrochloric | 5 |
| Color | Reddish Yellow | Bleeding in Xylene | 5 |
| Appearance | Powder | Bleeding in Ethyl Alcohol | 5 |

Bleeding in solvents (1 - 5 scale)

1 = Considerable bleeding

5 = No bleeding

NOTES:

* Acid-refined linseed oil with an acid value of 7.5-8.5 mg KOH per gram of oil.

** 5% for organic pigments and 1% for inorganic pigments.

USES: For Air drying enamel paint and Industrial Paints

PACKING: 25 Kgs Bags.

HANDLING AND STORAGE: Keep away from eye and skin contact. Place in closed containers. Keep away from food. If contacted wash thoroughly.



Phone +(98)2188176126
Fax +(98)2188178946

info@atfav.com
http://www.atfav.com

No.42, Niko Ghadam Alley, North
Sohrevardi Avenue, Tehran, Iran